

Ref. : PetEx.Spec.08

“LIQUIFIED PETROLEUM GAS (LPG)” SPECIFICATIONS

S.NO	CHARACTERISTICS	REQUIREMENT FOR COMMERCIAL BUTANE PROPANE MIXTURE	DISCRIPTION
		Butane – Propane Mixture	85
1.	Vapour Pressure at 40°C in KPa Gauge Max (Note 1)	1050 (Note 2)	D1267
2.	Volatility : Evaporation temp. in °C for 95% by vol.at 760 mm Hg pressure	2.0	D1837
3.	Total volatile Sulphur ppm Max.	150	D2784 D3246
4.	Copper Strip corrosion at 38°C for 1 hour	Not worse than No. 1	D1838
5.	Hydrogen Sulphide	Pass	D2420 (Note 3)
6.	Free water content	None	Visual

LPG Marketed in India confirms to BIS Specification IS 4576 : 1999 and Amendment No. 1 May 2003 Specification for Liquified Petroleum Gases.

To buy the product in PetEx, Following conditions need to be fulfilled:

- a. The Purchaser should be a member of PetEx.
 - b. The Member should pay EMD (Margin money) of the price of product, as stated in the contract.
 - c. The Member should have valid GST Registration
 - d. Buyer should have valid storage Explosive licences and other Licences / permissions from Local civil authorities like DM, Fire dept., Pollution,
 - e. The buyer should have all other valid licences for his factory / storage premises.
2. For any clarification on membership, product and procedure, you may call to Mr. Nilesh – M : 9920494214 or logon to www.petexindia.com.