

Ref: PetEx.Spec.014

BITUMEN VG 30 SPECIFICATIONS

Sr.No.	Parameters	Test Method	Standard Specification	Observations / Reported Value
1.	Penetration at 25°C, sec 100g, 0.1 mm	ASTM D 5	50-70	55
2.	Absolute Viscosity @60°C, Poise	ASTM D 2171	Min 2400	2800
3.	Kinematic Viscosity @135°C, cSt	ASTM D 2170	Min 350	360
4.	Flash Point	ASTM D 92	Min 220	290
5.	Solubility in Trichloroethylene, %	ASTM D 2042	Min 99	99.7
6.	Softening Point (R&B), °C	ASTM D 36	Min 47	49
7.	Ductility @25°C after RTFOT	ASTM D 113	Min 40	>95

1. To buy the product in PetEx, following conditions need to be fulfilled:

- a. The Purchaser should be a member of PetEx.
- b. The Member should pay EMD (Margin money) of the price of product, as stated in the contract.
- c. The Member should have valid GST Registration
- d. The buyer should have all other valid license for his factory / storage premises.
- e. The Product with this specification is offered for sale.

2. For any clarification on membership, product and procedure, you may call to Mr. Nilesh – M : 9920494214 or logon to www.petexindia.com.