

Ref: PetEx.Spec.018

FURNACE OIL SPECIFICATIONS

Sr.No.	Parameters	Test Method	Standard Specification	Observations / Reported Value
1.	Acidity Inorganic	P: 2	NIL	NIL
2.	Ash, % wt. MAX	P: 4	0.1	0.1
3.	Gross Calorific Value Max	P: 6 & P: 7	Typical	Typical
4.	Density @ 15°C	P: 32	Typical	Typical
5.	Flash Point: PMCC, DEG C, MIN	P: 21	66	66
6.	Kinematic Viscosity @50°C (CST)	P: 25	125 min 180 max	125 min 180 max
7.	Sediment % Wt., MAX	P: 30	0.25	0.25
8.	Total Sulphur, Wt. MAX	P: 33 & P: 35	4	4
9.	Water Content % Vol, MAX	P: 40	1	1

1. To buy the product in PetEx, following conditions need to be fulfilled:

- a. The Purchaser should be a member of PetEx.
- b. The Member should pay EMD (Margin money) of the price of product, as stated in the contract.
- c. The Member should have valid GST Registration
- d. The buyer should have all other valid license for his factory / storage premises.
- e. The Product with this specification is offered for sale.

2. For any clarification on membership, product and procedure, you may call to Mr. Nilesh – M : 9920494214 or logon to www.petexindia.com.